

EKP-4016/EKP-4016PB

Expansion Keypanel




The EKP-4016/4016PB is a 1 RU expansion panel used to give an additional 16 keys per unit attached. Up to seven EKPs can be connected. Part of the KP-Series keypanel family, the EKP-4016/4016PB provides exclusive superior digital audio by using OMNEO media networking technology (developed by RTS parent company Bosch and incorporating Dante™ high-quality audio of IP) as well as analog technology.


Features

- Wide-viewing angle color screen
- Ergonomic lever keys for talk/listen

Line Drawing



Front Panel View



Rear Panel View

Specifications

LCD Display

- Active Area
 - 120.10mm (wide) x 18.77mm (high)
- Dot Resolution
 - 576 x 90 pixels
- Color Resolution
 - 16-bit (64K) RGB color
- View Angle
 - 80 degrees (typical; all directions)

Weight

2.91lb (1.32kg)

Power Consumption

@110VAC –

@220VAC –

Input Power


100~240VAC, 50–60Hz

Connector

- EXP IN
- EXP OUT


General

- Storage Temperature
 - 40°C to 70°C (-40°F to 158°F)
- Operating Temperature
 - 0°C to 55°C (32°F to 131°F)
- Dimensions
 - 441.82mm W x 43.8mm H x 98.5mm D
 - (17.39" x 1.72" x 3.92")



KP-4016 Rear Panel View

Connect J9 on the KP-4016/4016PB to J8 on the EKP-4016



EKP-4016 Rear Panel View

Order Information

EKP-4016 • EKP 4016 EXPANSION PANEL

EKP-4016PB • EKP 4016 EXPANSION PUSHBUTTON PANEL

KP_OEI_PS_BRK • KP-OIE2 POWER SUPPLY BRACKET (USE WITH GlobTEK TR9CI2500MLDI30-N(RVB))

KP PS BRK LEV VI • KP PWR SUPPLY MNT BRKT LVL 6 (USE WITH GlobTEK TR9CI2500ML3-CIM(R6B))

The specification information is subject to change without notification. Brand names mentioned are the property of their respective companies.