



VC-TR60A

4K Dual Lens Voice Tracking Camera

Key Features

- 4K Dual Lens with 12x Optical Zoom
- Smart Voice Tracking with Built-in Microphone
- Picture in Picture Function

Product Specifications

PTZ Camera	
Sensor	1/2.8" 8.51M
Video Format	2160p : 60 / 50 2160p : 30 / 25 1080p : 60 / 50 / 30 / 25 720p : 60 / 50 / 30 / 25 1080i : 60 / 50
Video Output (HD) Interface	HDMI / Ethernet / 3G-SDI / USB
Optical Zoom	12x
Digital Zoom	8x
Horizontal Viewing Angle	81°
Vertical Viewing Angle	50.5°
Diagonal Viewing Angle	88.9°
Aperture	F1.8 ~ F3.6
Focal Length	3.4 ~ 43.3 mm
Shutter Speed	1/25 ~ 1/10,000 sec
Minimum Object Distance	Tele:1.5m / Wide:1m
Video S/N Ratio	> 50dB
Minimum Illumination	0.5Lux (F1.8, AGC ON)
Focus System	Auto / Manual
Gain Control	Auto / Manual
White Balance	Auto / Manual
Exposure Control	Auto / Manual
WDR	Yes
3D NR	Yes
Image Flip	Yes
PIP	Yes
Auto Tracking	Yes
Voice Tracking	Yes
Auto Framing	Yes
Panoramic Camera	
Sensor	1/2.8" 8.51M
Video Format	1080p : 60 / 50 / 30 / 25
Horizontal Viewing Angle	110°
Vertical Viewing Angle	78°
Aperture	F2.0
Focal Length	f=1.89mm

Pan & Tilt	
Panning Angle	+170° ~ -170°
Panning Speed	0.1°~100°/sec
Tilting Angle	+90° ~ -30°
Tilting Speed	0.1°/s ~ 60°/sec
Preset Positions	256
Output	
HDMI/3G-SDI	2160p 60 / 1080p 60
IP Stream	Main : 2160p 30 Second : 480p 30
IP Compression	H.264
USB Output	2160p 30
USB Compression	H.264 / MJPEG / NV12
Network	
IP Protocol	HTTP / RTSP / RTMP / RTMPS / SRT
PoE	PoE+ (IEEE802.3at)
Audio	
Audio Input	Line In
Audio Output	Ethernet / USB / HDMI / SDI
Audio Compression Format	AAC / PCM
Camera Control	
Interface	RS-232 / Ethernet / USB
Protocol	VISCA / ONVIF
UVC	Yes
UAC	Yes
General	
DC In	12V +/- 20%
Power Consumption	PoE: 15W DC In: 14W
Body Color	Black / White
Weight	1.5 kg
Dimension (WxHxD)	190 ×185 ×144 mm

