

DMM8 U (UL, ULD)

PROFESSIONAL DIGITAL AUTOMATIC MICROPHONE MIXER



THIS IS ALL YOU NEED

Engineered and made in Germany, the DMM8 U digital automatic microphone mixer is ideal for large meetings and conferences. Its DSP function ensures precise mixing of up to 80 channels by cascading up to 10 DMM8 U mixers. Two additional stereo audio outputs and one stereo USB offer additional routing options. Due to high signal-to-noise ratio, the DMM8 U also keeps noise from multiple open microphones to a minimum. Numerous DSP functions such as filters, compressor/limiter, ducking and routing make the DMM8 U a great fit in a variety of spoken word applications.

The UL version offers a LAN interface via Ethernet to enable the control over large distances using, for instance, an AMX control system.

In the ULD version, incorporating a highly sophisticated DANTE chip, all ins are available as direct outs, making it an outstanding tool for broadcast applications, while all outs are also available on the DANTE stream.

In total the DMM8 ULD provides 14 free assignable DANTE outs. Additionally, 4 DANTE streams can be used as inputs.

HIGHLIGHTS

- » **12 band graphic EQ on outputs**
for optimized loudspeaker tuning
- » **6 programmable presets**
for easy/fast tailoring to different situations
- » **Two channel USB streaming In and Out**
to interface with IT networks
- » **Up to 10 units cascadable**
for simultaneous use of up to 80 channels
- » **Digital signal processing and sophisticated mixing algorithm**
to feed in e.g. a laptop signal for wireless multimedia presentations
- » **Audio matrix routing of all inputs to all outputs**
for creating multiple mixes of multiple output combinations

APPLICATIONS

- » Large meeting areas
- » Conferencing
- » Round table discussions in TV shows

KEY SPECIFICATIONS

Number of input channels (6x analog, 2x USB, 4x DANTE)

All analog inputs phoenix type

U and UL version:

6x: Line, Mic, Aux, mono, stereo USB (= 2 channels)

ULD version:

4 channels DANTE

Number of output channels (2x analog, 2x USB, 14x DANTE)

U and UL version:

Out, Rec and USB out. Each 2 channels.

ULD version:

8x direct out from analog inputs and USB in to DANTE

Out, Rec, USB out to DANTE

DSP functions

Treble, Bass, Low Cut, Limiter, Compressor, Automix, Priority, Pan/Balance, Delay

Presets

6 free programmable presets

Phantom power

+ 48 V, max. 10 mA per input

Type

symmetrical

Level

- 60 dBu to 0 dBu

FRQ range

+/- 3 dB 20Hz – 20 kHz

THD & N

< 0.1%

Noise level (22 Hz – 22 kHz, QPK)

< -120 dBu

Dynamics

> 100 dB

Distortion headroom

20 dB

S/N (22 Hz - 22 kHz, RMS, A-Filter)

> 90 dB

Included accessories

Power cable

Item number

DMM8 U

6500H00230

DMM8 UL

6500H00240

DMM8 ULD

6500H00250



AKG ACOUSTICS GMBH LAXENBURGER STRASSE 254, 1230 VIENNA/AUSTRIA
AKG ACOUSTICS, U.S. 8400 BALBOA BOULEVARD, NORTHRIDGE, CA 91329, U.S.A.

© 2015 HARMAN International Industries, Incorporated. All rights reserved. AKG is a trademark of AKG Acoustics GmbH, registered in the United States and/or other countries.

Features, specifications and appearance are subject to change without notice.